

- *Brand: NOELIFT
- * Model: CPD-HK25
- * Chassis Number: HK20BTM1530, HK20BTM1531
- * Load Capacity: 2500kg
- * Dimensions: 2535x1170x2125mm, 6.3CBM, 3500kg
- * Fuel type: electric
- * Amperage: 80V/125Ah
- * www.globalagro.com.bo

2.5 ton 3m Economic lithium electric forklift				Pictures
	Standard			
1	Brand		NOELIFT	
2	Model		CPD-HK25	
3	Rated capacity	kg	2500	
4	Load center	mm	500	
5	Driving style		seated	
	Wheel			
6	Wheel type		Pneumatic tire	
7	Front wheel		7.00-12-12PR	
8	Rear wheel		6.00-9-10PR	
9	Number of wheels, front/rear(x=drive wheel)		2x/2	
10	Front tread	b10(mm)	970	
11	Rear tread	b11(mm)	960	
12	Wheelbase	y(mm)	1650	
13	Front Overhand	x(mm)	460	
	Dimension			
14	Lift height	H3(mm)	3000	
15	Mast type		normal 2-stage masts	
16	Mast tilt angle	α/β (deg)	6\12	
17	Free lift height	H2(mm)	130	
18	Mast extended height with load-backrest	H4(mm)	4035	
19	Mast closed height	H1(mm)	2005	
20	Overhead guard height	H6(mm)	2125	
21	Overall length	L1(mm)	3615	
22	Length to fork face	B1(mm)	2535	
23	Overall width	H2(mm)	1170	
24	Fork size	L/E/S (mm)	1070/122/40	
25	Fork outside width	B5(mm)	250~1040	
26	Mast ground clearance	M1(mm)	110	
27	Aisle width for pallet 800*1200	Ast(mm)	3920	
28	Turning radius	mm	2335	
	Performance			
29	Driving speed(load/unload) Hydraulic	km/h	10/12	
30	Lifting speed with load	MM/SEC	300/400	

31	Downing speed with load	MM/SEC	470/450
32	Max.gradeability	%	15/20
33	Service weight	KG	3500
Engine			
34	Model		Lithium Battery
35	Battery capacity	V/AH	80V/125AH
36	Driving motor(S2-60min)	kw	AC8
37	Lifting motor(S3-15%)	kw	AC10
38	Steering system		Hydraulic type

